



Accessories (Octos)

RPS-156/B

Power supply

Power supply; 230 V → 15 VDC; 6A

Art.No. 10450128

Standard article

This article is available from stock, barring to unforeseen circumstances



Housing RPS-156B front



Housing RPS-156B back

	Port	Range	Min.	Typical	Max. Unit	Rem.	Margin
Connectors	In			DIN 41612 H15			
	Out			DIN 41612 H15			
Temperature Range			0		+70 °C		
Indicator	Output Voltage			LED green			
Equipment Approval				CE			
Efficiency			77		86 %		
Current AC	Rush-in	Cold condition			25 A AC	1	
		Hot Condition			35 A AC	1	
Fuse	In			3,15	A	3	
Input Voltage			94	230	264 VAC		
Power Reduction	-	from 50 °C		2,5	%/K		
Output Voltage			+14,5	+15	+15,5 VDC		
EMC	Mains feedback			EN-61000-3-2: 1995 Class D			
	Interference suppression			EN-50082-2: 1992 ENV-50204			
	Interference immunity			EN-61000-4- 2/3/4/5/6/11			
	Interference emission			EN-50081-1: 1992 EN-55011/55022: Class B			
Output Current					6 A	2	

Remarks:

- 1 Peak current
- 2 Switches off at 110% of nominal current, permanent short-circuit proof.
- 3 Slow blow model fuse.

PRELIMINARY SPECIFICATIONS. CHECK OUR SALES SUPPORT DEPARTMENT FOR POSSIBLE CHANGES

spec version: 01
print-date: 15-12-2003

603