



Art.No. 10450136

Standard article

This article is available from stock, barring to unforeseen circumstances

Accessories (Octos)

RPS-244

Power supply

Supply for nodecombining system, 230 VAC input, 24V output.



RPS-244



RPS-244

	Port	Range	Min.	Typical	Max. Unit	Rem.	Margin
Connectors	In			DIN 41612 H15			
	Out			DIN 41612 H15			
Temperature Range			0		+70 °C		
Indicator	Output Voltage			LED green			
Equipment Approval				CE			
Efficiency				77	86 %		
Current AC	Rush-in	Cold condition			25 A AC	1	
		Hot Condition			35 A AC	1	
Fuse	In			3,15	A	3	
Input Voltage			94	230	264 VAC		
Power Reduction	-	from 50 °C		2,5	%/K		
Output Voltage			+23,5	+24	+24,5 VDC		
EMC	Mains feedback			EN-61000-3-2: 1995 Class D			
	Interference suppression			EN-50082-2: 1992 ENV-50204			
	Interference immunity			EN-61000-4- 2/3/4/5/6/11			
	Interference emission			EN-50081-1: 1992 EN-55011/55022: Class B			
Output Current					4,2 A	2	

Remarks:

- 1 Peak current
- 2 Switches off at 110% of nominal current, permanent short-circuit proof.
- 3 Slow blow model fuse.

note: Specifications are measured at room temperature

spec version: 01

print-date: 11-01-2006

851