



Art.No. 10930541

## OEM article

This article is made on customer specifications and not available for delivery

TLT+ series

# TLT-2-8+/FI-T

2-way tap

Tap loss 8 dB, F female input connector, terminated



TLT-2-8+/FI-T

	Port	Range	Min.	Typical	Max. Unit	Rem.	Margin
Frequency Range	-		5		862 MHz		
Equipment Approval				CE			
Tap Loss	In -> Tap	5 MHz < F < 550 MHz		7,4	8 dB		
		550 MHz < F < 862 MHz		7,5	8,5 dB		
Return Loss	In/Tap	5 MHz < F < 40 MHz	22		dB		
		40 MHz < F < 862 MHz	22		dB	2	
Isolation	Tap -> Tap	5 MHz < F < 470 MHz	30		dB		
		470 MHz < F < 862 MHz	25		dB		
Screening Effectiveness	-	5 MHz < F < 300 MHz	85	95	dB	1	
		300 MHz < F < 470 MHz	80	90	dB	1	
		470 MHz < F < 862 MHz	75	85	dB	1	

### Remarks:

- 1 Transfer Impedance Method according IEC 60728-2(5-30 MHz)  
Absorption clamp method according IEC-60728-2 § 4.4 (30-1000 MHz)
- 2 F > 40 MHz -1.5 dB/oct

note: Specifications are measured at room temperature

spec version: 01  
print-date: 03-01-2007