



## TLT-4-8/FI-T

4-way tap

Tap loss 8 dB, F female input connector, terminated

Art.No. 10930550

### Special article

This article is not available from stock. Please call us for delivery possibilities



TLT-4-8/FI-T

	Port	Range	Min.	Typical	Max. Unit	Rem.	Margin
<b>Frequency Range</b>	-		5		1000 MHz		
<b>Equipment Approval</b>				CE			
<b>Tap Loss</b>	In -> Tap	5 MHz < F < 550 MHz		7	8 dB		
		550 MHz < F < 862 MHz		7,5	8,5 dB		
		862 MHz < F < 1000 MHz		8	9 dB		
<b>Return Loss</b>	In	5 MHz < F < 550 MHz	18				dB
		550 MHz < F < 1000 MHz	16				dB
	Tap	5 MHz < F < 15 MHz	16				dB
		15 MHz < F < 550 MHz	18				dB
		550 MHz < F < 1000 MHz	16				dB
<b>Isolation</b>	Tap -> Tap	5 MHz < F < 15 MHz	20	26			dB
		15 MHz < F < 40 MHz	26	30			dB
		40 MHz < F < 550 MHz	24	30			dB
		550 MHz < F < 1000 MHz	20	26			dB
<b>Screening Effectiveness</b>	-	5 MHz < F < 300 MHz	85	95			dB 1
		300 MHz < F < 470 MHz	80	90			dB 1
		470 MHz < F < 1000 MHz	75	85			dB 1

**Remarks:**

- 1 Transfer Impedance Method according IEC 60728-2(5-30 MHz)  
Absorption clamp method according IEC-60728-2 § 4.4 (30-1000 MHz)

note: Specifications are measured at room temperature

spec version: 02

print-date: 25-05-2005

201