



TLT series

TLT-8-11/FI-T

8-way tap

Tap loss 11 dB, F female input connector, terminated

Art.No. 10390560

Special article

This article is not available from stock. Please call us for delivery possibilities



TLT-8-11/FI-T

	Port	Range	Min.	Typical	Max. Unit	Rem.	Margin
Frequency Range	-		5		1000 MHz		
Equipment Approval				CE			
Tap Loss	In -> Tap	5 MHz < F < 40 MHz		10,5	11 dB		
		40 MHz < F < 550 MHz		10,5	11,5 dB		
		550 MHz < F < 862 MHz		10,5	11,8 dB		
		862 MHz < F < 1000 MHz		11,5	12,2 dB		
Return Loss	In	5 MHz < F < 1000 MHz	18			dB	
	Tap	5 MHz < F < 1000 MHz	18			dB	
Isolation	Tap -> Tap	5 MHz < F < 40 MHz	25	28		dB	
		40 MHz < F < 550 MHz	22	30		dB	
		550 MHz < F < 1000 MHz	20	26		dB	
Screening Effectiveness	-	5 MHz < F < 300 MHz	85	95		dB	1
		300 MHz < F < 470 MHz	80	90		dB	1
		470 MHz < F < 1000 MHz	75	85		dB	1

Remarks:

- 1 Transfer Impedance Method according IEC 60728-2(5-30 MHz)
Absorbion clamp method according IEC-60728-2 § 4.4 (30-1000 MHz)

note: Specifications are measured at room temperature

spec version: 03

print-date: 25-05-2005

208