

TLT-8-17/FI


8-way tap

Tap loss 17 dB, F female input connector

Art.No. 10390562

Special article

This article is not available from stock. Please call us for delivery possibilities



TLT-8-17/FI

	Port	Range	Min.	Typical	Max. Unit	Rem.	Margin
Frequency Range	-		5		1000 MHz		
Equipment Approval				CE			
Insertion Loss	In -> Out	5 MHz < F < 15 MHz		2,3	2,6 dB		
		15 MHz < F < 40 MHz		2	2,5 dB		
		40 MHz < F < 550 MHz		2	2,8 dB		
		550 MHz < F < 1000 MHz		2,8	3,5 dB		
Tap Loss	In -> Tap	5 MHz < F < 40 MHz		16	16,5 dB		
		40 MHz < F < 550 MHz		15,7	16,7 dB		
		550 MHz < F < 862 MHz		16	18 dB		
		862 MHz < F < 1000 MHz		17	18,5 dB		
Return Loss	In	5 MHz < F < 1000 MHz	18			dB	
	Out	5 MHz < F < 1000 MHz	18			dB	
	Tap	5 MHz < F < 1000 MHz	18			dB	
Isolation	Out -> Tap	5 MHz < F < 40 MHz	30			dB	
		40 MHz < F < 550 MHz	29			dB	
		550 MHz < F < 1000 MHz	26			dB	
	Tap -> Tap	5 MHz < F < 40 MHz	25	28		dB	
		40 MHz < F < 550 MHz	22	30		dB	
		550 MHz < F < 1000 MHz	20	26		dB	
Screening Effectiveness	-	5 MHz < F < 300 MHz	85	95		dB	1
		300 MHz < F < 470 MHz	80	90		dB	1
		470 MHz < F < 1000 MHz	75	85		dB	1

Remarks:

- 1 Transfer Impedance Method according IEC 60728-2(5-30 MHz)
Absorption clamp method according IEC-60728-2 § 4.4 (30-1000 MHz)

note: Specifications are measured at room temperature

spec version: 02

print-date: 25-05-2005

212