


Art.No. 30400563

## Standard article

This article is available from stock, barring to unforeseen circumstances



WS-02 front

	Port	Range	Min.	Typical	Max. Unit	Rem.	Margin
<b>Frequency Range</b>			5		2150 MHz		
<b>Connectors</b>	In			F-female			
	Out			F-female			
<b>Equipment Approval</b>				CE			
<b>Insertion Loss</b>	In -> Out	10 MHz < F < 47 MHz			4,5 dB		
		47 MHz < F < 862 MHz			4,5 dB		
		862 MHz < F < 1750 MHz			6,0 dB		
		1750 MHz < F < 2150 MHz			6,5 dB		
<b>Return Loss</b>	In	10 MHz < F < 47 MHz	12		dB		
		47 MHz < F < 862 MHz	12		dB		
		862 MHz < F < 1750 MHz	12		dB		
		1750 MHz < F < 2150 MHz	12		dB		
	Out	10 MHz < F < 40 MHz	10		dB		
		40 MHz < F < 470 MHz	10		dB		
		470 MHz < F < 862 MHz	10		dB		
		862 MHz < F < 1750 MHz	10		dB		
		1750 MHz < F < 2150 MHz	7		dB		
<b>Isolation</b>	Out -> Out	10 MHz < F < 40 MHz	12		dB		
		40 MHz < F < 470 MHz	16		dB		
		470 MHz < F < 862 MHz	16		dB		
		862 MHz < F < 1750 MHz	15		dB		
		1750 MHz < F < 2150 MHz	13		dB		

#### Remarks:

\* All ports are power pass (out-in) (DC30V 1A max)  
 note: Specifications are measured at room temperature

spec version: 01  
 print-date: 15-12-2003

175