

2-way tap

WTP-222/TI

Features:

- Test & Insertion point



Description

The WTP-222/TI is a passive wideband Tap. It combines 1 tap I/O port and 1 normal I/O port to 2 common port. There is a 20 dB test point and a 20 dB insertion point at the common port.

The unit is supplied with F connectors for the RF and BNC connectors for the test and insertions points. Dimensions of the cassette is 3,5 TE so 24 units can be placed into a standard 19 inch rack. (84TE)

Specifications

V1 mrt 13, 2009

	Port	Range	Min	Typical	Max	Units	Remark
Frequency Range		I/O to Common	5		1000	MHz	
Flatness Tap		862 MHz < F < 1000 MHz			+/-1.0	dB	
		5 MHz < F < 862 MHz			+/- 0,5	dB	
Connectors		I/O Back Panel		F-female			2
		Common Back Panel		F-female			2
		Test point Front Panel		BNC female			
		Insertion point Front Panel		BNC female			
Temperature Range		operational	10		+55	°C	
Humidity Range		Non condensing	5		95	%	
EMC		470 MHz < F < 1000 MHz	65	75		dB	3
		300 MHz < F < 470 MHz	75	80		dB	3
		5 MHz < F < 300 MHz	75	85		dB	3
Dimensions	Outline	3HE x 3,5TE x 70		H x W x D		mm	

Ordering Information

WTP-222/TI	2-way tap	Article number:	11204814
MRO-70	19" Mounting Panel	Article number:	11101070

	Port	Range	Min	Typical	Max	Units	Remark	
Return Loss	All ports	40 MHz < F < 1000 MHz	20			dB	1	
Insertion Loss	I/O 1 to Common	5 MHz < F < 40 MHz	20			dB		
		5 MHz < F < 862 MHz			13	dB		
	I/O 2 to Common	862 MHz < F < 1000 MHz				7,5	dB	
		5 MHz < F < 862 MHz				12	dB	
Isolation	Testpoint Insertion Point	862 MHz < F < 1000 MHz			7	dB		
		5-862 MHz w.r.t. Common		20		dB		
	Input to Input	5 MHz < F < 600 MHz	30			dB		
Vibration test		601 MHz < F < 1000 MHz	25			dB		
Marking		EN 60068; 2-6 2008						
		CE / RoHs compliant						

Remarks	
1	At F = 40 MHz F > 40 MHz - 1,5 dB/octave
2	F connectors according to IEC 60169-24, acceptable for diameters between 0,58mm through 1,0mm Spacing: F connectors 17 mm BNC connectors 34 mm
3	According IEC 60728-2; 4.4 (30 - 1000 MHz) IEC 60728-5 (5 - 30 MHz)