

Fly lead

RL75-21-7.5



Specifications

V1 sep 17, 2002

	Port	Range	Min	Typical	Max	Units	Remark	Margin
Frequency	None		5	IEC-male angled	1000	MHz		
Connectors		-		IEC-female angled				
Impedance	Colour			White				*
Outer diameter	Diameter			75		Ohm		
Assembly Length				4.8		mm		
Equipment Approval				7.5		m		
				CE				

Ordering Information

RL75-21-7.5	Fly lead	Article number:	10470214
-------------	----------	-----------------	----------

Specifications V1 sep 17, 2002

	Port	Range	Min	Typical	Max	Units	Remark	Margin
Insertion Loss	In -> Out	5 MHz < F < 470 MHz		2.2	2.5	dB		
		470 MHz < F < 1000 MHz		3.2	3.5	dB		
Return Loss		5 MHz < F < 1000 MHz	18			dB	1	
Screening Effectiveness		5 MHz < F < 300 MHz	75	85		dB	2	
		300 MHz < F < 470 MHz	75	85		dB	2	
		470 MHz < F < 1000 MHz	65	75		dB	2	

Remarks	
1	F > 40 MHz -1.5 dB/oct
2	Transfer impedance method according IEC 60728-2 (5-30 MHz) Absorbion clamp method according IEC-60728-2 § 4.4 (30-1000 MHz)
*	Standard colour cable & connectors: white. Other colours on request.